

## Nanaimo Telehandler License

Nanaimo Telehandler License - A telescopic handler or telehandler is a machine that is frequently used in industrial and agricultural applications. It has a similar look to a lift truck and even functions in a similar manner, even if, the telehandler is more of a crane than a lift truck. It has a telescopic boom which could extend forward and upward from the motor vehicle. The boom has the capability to fit one of several attachments like a bucket, a lift table, muck grab or pallet forks.

Pallet blades are the most popular accessory for the telehandler. This particular equipment is normally utilized for transporting loads to and from places that a traditional forklift would find inaccessible. Telehandlers are specially helpful for placing loads on rooftops for example, or for removing palletized cargo from with a trailer. Many of the tasks that a telehandler can accomplish would otherwise need a crane and this piece of equipment can be costly, not always time efficient and not practical.

Because the boom extends or raises while bearing a load, it also acts as a lever. Even with the counterweights in the back, this causes the machine to become more and more unbalanced; hence, the advantage of the telehandler is really its greatest limitation. As the working radius increases, the lifting capacity lessens. The working radius is defined as the distance between the front of the wheels and the center of the load.

The telehandler with a 5000 lb capacity for instance, with a retractable boom can safely lift as little as 400 lb at a fully extended boom at a low boom angle. Equivalent machinery with a lift capacity of 5000 lbs and a retractable boom which could support as much as 10,000 lb with the boom raises to around 70 degrees. The operator has a load chart to help determine whether a particular lifting job can be done in an efficient and safe manner. This chart considers the weight, height and the boom angle.

Many telehandlers come equipped with a computer which uses sensors to be able to monitor the vehicle. These sensors would alert the operator and some are capable of cutting off further control input if the limits of the vehicle are exceeded. Some telehandler types are also outfitted together with front outriggers which are known as mobile cranes. These significantly extend the lifting capacity of the equipment while it is stationary.