Nanaimo Loader Ticket

Nanaimo Loader Ticket - Loaders have been created to operate just about anyplace. They offer optimal traction and maneuverability due to a heavy-duty oscillating joint which provides forty five degree turning angles to the right and left, with 10 degrees of oscillation in both directions. Access is granted to confined and tight spaces by narrow machine widths. Majority of skid-steer loaders with similar operating capacities are unable to compete. The bucket and tires on the Gehl equipment follow a steady turn radius also. This means the back tires of the loader follow the path of the front tires.

Fantastic hydraulic performance, along with numerous time-saving features on the Gehl articulated loaders, offers customers with the hydraulic precision and power they have come to expect from all of the Gehl equipment. Lift arm and bucket float features allow these equipment to execute light scraping and rearward leveling actions. Flat-face couplers, together with the two easily accessible auxiliary hydraulic lines power numerous instruments and make changing the accessories an easy job to perform.

Gehl articulated loaders have uniquely built lift arms which are made to attain great visibility, maximum strength and fast cycle times. The specific linkage design makes it possible for for mechanized self-leveling action in either the upward and downward directions. It can also easily perform exceptional bucket dump angles at the mid and top ranges of the hoist path as well as offering excellent forward reach. Models 340 and 140 have parallel kind linkage and the model 540 has "Z" bar kind linkage. These linkage patterns provide fantastic bucket breakout forces from 2433lbs on the 140 model to 10,749lbs on the model 540.

Gehl articulated loaders are popular world-wide for their ease of operation, supreme ergonomics and unsurpassed visibility. The 540 and 340 machines have a complete cab enclosure preference obtainable. This offers better comfort and safety for the person operating it. Secure operation and 360 degree visibility is sustained by placing the one operating it higher than the load to guarantee an exceptional viewpoint of the accessory. An inching pedal allows the person operating it to alter ground speed whilst maintaining a fixed engine speed. This feature allows the operator to properly run accessories while ensuring precise machine velocity control. A multi-function direction control controls the bucket, travel direction, float, differential lock and auxiliary hydraulic functions as well as the lift arm.